

## **9U Cabinet [600\*450]**

A 9U [600x450] network cabinet is a standard wall-mounted enclosure designed to house 19-inch rack-mount equipment, typically featuring a **600mm width**, **450mm depth**, and a **load capacity of around 60 kg**.

### **Technical Specifications**

<b>Attribute</b>	<b>Specification</b>
<b>Height</b>	9U (rack units)
<b>External Dimensions</b> (WxDxH)	~600 mm x 450 mm x 500-502 mm
<b>Mounting Standard</b>	19-inch, compliant with ANSI/EIA RS-310-D, IEC297-2, DIN41494 standards
<b>Material</b>	SPCC cold-rolled steel (thickness varies by component, typically 0.9mm to 2.0mm)
<b>Loading Capacity</b>	Typically <b>60 kg</b> (some models can support up to 91 kg)
<b>Degree of Protection</b>	IP20
<b>Door Type</b>	Lockable, available with tempered <b>glass</b> or <b>perforated</b> steel options; reversible (opens left or right)
<b>Side Panels</b>	Removable for easy access, often with a 'Click' or simple lock mechanism

---

<b>Cable Entry</b>	Entry points available at the top cover and bottom panel
<b>Ventilation</b>	Ventilation holes are common, with options to install cooling fans in the top panel
<b>Color/Finish</b>	Matt Black (RAL 9005) is standard, with powder-coat paint finish
<b>Mounting Type</b>	Wall mounted (can be free-standing with optional casters)

---