

22U Cabinet (600*800) with D-Ring Cable Manager and 6 Way PDU PLASTIC

Comes in 4 Parts : Frame/ Top & Bottom / Glass Door & Back / Side Panel

A generic datasheet for a 22U cabinet (600mm*800mm) with D-Ring Cable Managers and a 6-Way Plastic PDU includes key details on its physical dimensions, material, included accessories, and load capacity. This information is typical for a floor-standing network cabinet that comes flat-packed for self-assembly.

General Specifications

Attribute	Specification
Size	22U
External Dimensions (H x W x D)	~1150-1170 mm x 600 mm x 800 mm (including castors/feet)
Material	SPCC cold-rolled steel
Construction	Detachable composite structure / Flat-packed for assembly
Static Loading Capacity	Typically 800 kg (with leveling feet)
Color	Black (RAL 9005) or Grey (RAL 7035) powder coated finish
Standard Compliance	ANSI/EIA RS-310-D, IEC297-2, DIN41494
IP Protection Grade	IP20

Net Weight	~61 - 70 kg
-------------------	-------------

Components & Accessories

- **Frame:** The main structure is typically made of 1.2 mm thick steel.
- **Top & Bottom Panels:** Includes cable entry points with removable plates and ventilation holes.
- **Front Door:** Lockable tempered glass door with a steel frame, reversible (can open from left or right).
- **Back Panel/Door:** Usually a solid or perforated metal door with a lock.
- **Side Panels:** Removable and lockable steel panels for easy service access.
- **Mounting Rails:** Four 19-inch adjustable-depth mounting profiles with "U" height markings, made of 2.0 mm thick steel.
- **PDU:** A 6-way (6-socket) plastic PDU (power strip) is included, with specifications like max current of 13 Amps and max output of 3250 Watts (for UK type outlets, specifications may vary by region).
- **Cable Management:** D-ring cable managers are typically included for vertical cable routing.
- **Included Accessories:** Usually comes with a set of casters (wheels), adjustable jacking/leveling feet, grounding kits, and a hardware kit (M6 screws and cage nuts).
- **Ventilation:** Provision for a roof-mounted fan tray (fans often included).