

32U Cabinet [600*800] - with D-Ring Cable Manager and 6 Way PDU PLASTIC Comes in 3 Parts : Frame/ Top & Bottom / Glass Door, Back & Side Panel

Here is the technical data sheet for a standard **32U Cabinet [600*800]**. Note that exact material thickness and specific PDU details might vary slightly by manufacturer.

Specification	Detail
Cabinet Type	Floor-standing network/server cabinet
Usable Height	32U
External Dimensions (H x W x D)	Approx. 1600-1610 mm x 600 mm x 800 mm
Material	High-quality SPCC cold-rolled steel
Material Thickness	Mounting profiles: 2.0 mm; Others: 1.0-1.2 mm
Static Loading Capacity	Typically 600 kg (on castors) to 800 kg (on adjustable feet)
IP Protection Class	IP20
Color	Matt Black (RAL 9004/9005) or light gray (RAL 7035)
Front Door	Tempered safety glass door with a lock and handle
Rear Door	Steel panel (solid or perforated mesh options available) with a lock

Side Panels	Removable and lockable
Mounting	19" adjustable mounting rails with U-markings
Cable Management	D-ring cable managers included; cable entry points on top and bottom with brush strips
Power Distribution Unit (PDU)	6-way plastic PDU included (UK type outlets, 13 Amps max current, 3250 Watts max output power)
Ventilation	Vented top/bottom panels; often includes a 4-fan cooling panel
Mobility	Adjustable leveling feet and heavy-duty casters with brake option included
Included Accessories	Mounting hardware (M6 screws & nuts), keys, grounding kits
Standards Compliance	Complies with ANSI/EIA RS-310-D, IEC297-2, DIN41491 (PART1, PART7), ETSI standards