

IP Camera Tester (IPC-1910plus)

Display & Interface

- **Screen:** 4-inch IPS touch screen.
- **Resolution:** 960 x 640 pixels.
- **Operation:** Capacitive touch screen and physical buttons.

Video Support

- **IP Camera:** Up to 8K H.265/H.264 video streams.
- **TVI/CVI/AHD:** Up to 8MP (4K) at various frame rates.
- **Analog:** CVBS PAL/NTSC testing.
- **PTZ Control:** RS485 protocol support.

Power Specifications

- **PoE Output:** 48V PoE, max power 25.5W.
- **DC Output:** DC 12V / 3A.
- **Battery:** 7.4V / 2600mAh Lithium-ion polymer battery.
- **Runtime:** Approximately 9 hours of continuous use.
- **Charging:** 3–4 hours charge time via DC 12V/1A.

Network & Communication

- **Wi-Fi:** Built-in 2.4GHz Wi-Fi (150Mbps).
- **LAN Port:** 10/100/1000M adaptive Ethernet.
- **Protocol Support:** ONVIF, RTSP, and custom private protocols for over 100 camera brands.

Testing & Utility Tools

- **Cable Testing:** UTP cable test (connection status and wire sequence).
- **Network Tools:** IP scan, PING, DHCP server, Link monitor, Port flashing.

- **Audio:** 1-channel audio signal input for testing.
- **Flashlight:** Integrated high-brightness LED.