

## Technical specification

- Model: NF-IPC722 & NF-IPC722ATCHS
- Touch Screen: 7 inch G+ G structure capacitance screen
- LCD Screen: 7 inch resolution 1920x1200 IPS HD full view
- Ethernet Port: 10/100/1000M adaptive
- WIFI: Built-in wireless WIFI, speed 150M
- IP Camera Test: 4K H.265 IP camera test, video image real-time display without delay, support video snapshot, recording and playback
- ONVIF: ONVIF tool, support DAHUA, HIKVISION, ACTI, SAMSUNG and other more than 30 manufacturer private protocols and customized, support camera mobile client installation
- PTZ Control: Support Pelco-D/P, Samsung, Panasonic, etc. more than 30 protocols
- CVBS Analog Camera Test: 1 channel CVBS analog signal input, support PAL/NTSC format adaptation
- HD Camera Test: Support HD TVI 8MP, CVI 8MP, AHD SMP, EX-SDI 8MP (Excluded on IPC722; only available on IPC722ADCHS)
- Video Image Zoom: Real-time enlarge moving HD video image, max enlarge 8 times
- Cable Test: Built-in cable testing tool, check cable sequences and breakpoints, etc
- Audio Test: One channel audio signal input for testing, can be recorded and saved
- Optical Power Meter: Test optical fiber parameters
- DC12V Power Output: DC12V power output, max current 3A, provide temporary power for cameras
- DC24V Power Output: DC24V power output, max current 1A, provide temporary power for cameras
- PoE Power Output: 48V standard PoE output, provide PoE power for cameras
- DC5V Power Output: Provide temporary power for USB-powered cameras or emergency power for mobile phones, max current 2A
- PSE Voltage Test: Display PoE power supply device voltage and circuit condition
- HDMI Video Input Test: Input HD video image into instrument to test video recorder; IPC722ATCHS supports up to 4K 30FPS and IPC722 supports only HD only.
- RS485 Serial Port tool: Can send or receive any data or hex data
- Power Charger: DC 12V/2A
- Battery: Built-in 7.4V polymer lithium battery, capacity 7000mAh, can work continually for 8-10 hours
- Language: Chinese Simplified, Chinese Traditional, English, Germany, Spanish, Portuguese, Russian, French, Polish, Korean, Japanese, Turkish and Italian 13 languages
- Internal SD Storage: 8G
- Working Temperature: -10°C - 50°C
- Working Humidity: 30%-90%
- External Size: 23emx14emx4.5em

- Weight: 0.9kg